

## Model information about cooker hoods

Miele							
Model name/ model ID number			DA 5620 D				
Configuration							
Vented/Recirculation			● / –				
Convertible for recirculation operation			–				
Rear wall fixing			–				
Ceiling fitting			●				
Housing unit fitting top/bottom/side			– / – / –				
Dimensions							
Product dimensions	Height	cm	90,0				
	Width	cm	119,8				
	Depth	cm	69,8				
Unit height including chimney piece	Vented	cm					
	Recirculation	cm					
Niche dimensions for assembly	Height	cm					
	Width	cm					
	Depth	cm					
Depth		cm					
Minimum		cm	55,0				
Minimum distance above gas hob		cm					
Features							
Vent connection top/rear/side <sup>1)</sup>			● / – / –				
Vent connection diameter			mm	150			
Non-return flap in unit			● /				
Fan adjustable infinitely/in stages (no.)			– / 3				
Intensive setting <sup>2)</sup>			●				
Flow rate <sup>3)</sup>							
Vented from – To			m³/h	200 - 480	-	-	-
Recirculation from – To			m³/h	-	-	-	-
Intensive setting vented/recirculation			m³/h	700 /	/	/	/
Net weight <sup>4)</sup>			kg	43,0			
Electrical specifications							
Voltage			V	230			
Wattage			W	280			
Fuse			A	10			
Connection cable length			cm				
Earthed plug/Fixed connection			/ ●				
Interference suppressed			●				
Mains interference free			●				
Name and address of supplier			Miele & Cie. KG, Postfach, 33325 Gütersloh				
Note:							
• Yes, available							
1) Precise dimension							
2) Short-term high ventilation rate in conjunction with higher noise level							
3) Depending on external fan							
4) When fitting under a wall unit or on the wall/ceiling, ensure that the wall unit and the wall/ceiling can support the weight of the cooker hood (including decor front if appropriate).							
Note: Table established 07/05. Subject to further development.							